

**Fanvil**



---

<b>1</b>	.....	<b>2</b>
<b>2 RTP</b>	.....	<b>3</b>



## 2 RTP

### 2.1

### 2.2


### 2.3

#### 2.3.1

The screenshot displays the Fanvil vCore web management interface. The top navigation bar includes tabs for '功能设定' (Function Settings), '媒体设置' (Media Settings), '组播' (Multicast), '功能' (Function), '时间/日期' (Time/Date), '提示音' (Tone), and '高级' (Advanced). A left sidebar lists various system settings categories, with '电话设置' (Phone Settings) currently selected. The main content area shows a configuration page for RTP settings. A red box highlights the 'RTP 设置 >>' section, which contains a checked checkbox for 'RTP 拨号:'. Below this, there is a section for '来电指定铃音类型设定(Alert-Info) >>' and a '提交' (Submit) button. On the right side, a 'NOTE' box provides a description: '描述: 媒体设置, 可以设置语音编码、音量、铃声等'.

## 2.3.2

272	2018-06-26 19:06:52	172.16.20.144	172.16.20.190	RTP	214 PT=ITU-T G.711 PCMU, SSRC=0x45ECF70B, Seq=48069, Time=3652666366
274	2018-06-26 19:06:52	172.16.1.2	172.16.20.144	SIP	556 Request: ACK sip:333@172.16.20.144:5060
275	2018-06-26 19:06:52	172.16.20.144	172.16.20.190	RTP	214 PT=ITU-T G.711 PCMU, SSRC=0x45ECF70B, Seq=48070, Time=3652666526
276	2018-06-26 19:06:52	172.16.20.144	172.16.20.190	RTD	214 DT-TTU-T G.711 PCMU, SSRC=0x45ECF70B, Seq=48070



Frame 284: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface 0  
Ethernet II, Src: 58:5d:64:59:8e:52 (58:5d:64:59:8e:52), Dst: 00:a8:59:db:06:0c (00:a8:59:db:06:0c)  
Internet Protocol Version 4, Src: 172.16.20.144, Dst: 172.16.20.190  
User Datagram Protocol, Src Port: 10002, Dst Port: 10002  
Real-Time Transport Protocol  
[Stream setup by SDP (frame 225)]  
10.. .... = Version: RFC 1889 Version (2)  
..0. .... = Padding: False  
...0 .... = Extension: False  
.... 0000 = Contributing source identifiers count: 0  
0.. .... = Marker: False  
Payload type: USA Federal Standard FS-1016 (1)  
Sequence number: 10304  
[Extended sequence number: 75840]  
Timestamp: 2835719753  
Synchronization Source identifier: 0x8670a79a (2255529882)  
00 a8 59 db 06 0c 58 5d 64 59 8e 52 08 00 45 00 ..V...X] dY.R..E.  
00 28 47 ae 00 00 b4 11 3d a8 ac 10 14 90 ac 10 ..(G.... =.....  
14 be 27 12 27 12 00 14 0a 97 80 01 28 40 a9 05 ..'...'...(@..  
a6 49 86 70 a7 9a 00 00 00 00 00 00 ..I.p....